

The power behind competitiveness

# Delta UPS—Amplon Family

INX Series, Standard and Long Backup Models, Single Phase  
1/ 2/ 3 kVA

## Reliability for the most critical moments

The INX series is an online double-conversion UPS providing consistent sine-wave power to your critical equipment's. The INX series features an input power factor corrector and best-in-class AC-AC efficiency of up to 90% resulting in greater energy savings.

The INX series leads the industry in combining compact size, availability, flexibility and low total cost of ownership.

## Availability

- True online double-conversion topology and zero transfer time to battery ensure high reliability
- High input power factor corrector (> 0.99) for controlled sine wave AC output
- Cold-start capability with temporary battery power when the utility power is out
- Automatic bypass to transfer the load on mains in case of overload & internal fault
- Battery deep discharge protection

## Flexibility

- Excellent local communications through user friendly LCD display
- Intelligent management software connectivity via RS232, mini slot or USB port
- Three multi-functional buttons for the operation and selection of parameters

## Low Total Cost of Ownership

- Long backup time model with super charger inside the UPS
- Protection against over voltage; charger working even when the input switch is in off position
- ECO mode to provide energy cost savings
- Wide input voltage range to reduce the chance of using the battery and to extend battery life
- Intelligent battery management sustaining battery life and performance
- Fan speed control by load level and room temperature to optimize performance



Server



Network



Security



Home  
Appliances



POS



Banking



Smarter. Greener. Together.

# Delta UPS—Amplon Family

INX Series, Standard and Long Backup Models, Single Phase  
1/ 2/ 3 kVA

Model		INX-1K	INX-2K	INX-3K
Power Rating		1kVA/0.8kW	2kVA/1.6kW	3kVA/2.4kW
Input	Nominal Voltage	230 Vac		
	Voltage range	110 ~ 300 Vac*		
	Frequency	40 ~ 70 Hz		
	Power Factor	> 0.99 @ nominal voltage (input voltage)		
Output	Power Factor	0.8		
	Voltage	200**/ 208**/ 220/ 230/ 240 Vac		
	Voltage Regulation	± 1% (Battery mode)		
	Frequency	47 ~ 53 Hz or 57 ~ 63 Hz (Synchronized Range)		
	Current Harmonic Distortion	≤ 3% (linear load); ≤ 6% (non-linear load)		
	Overload Capability	< 105%: Continuous; 105% ~ 110%: 10 minutes; 110% ~ 130%: 1 minute; > 130% only 3 seconds		
Receptacle	Standard Model	India socket x 3	India socket x 4	India socket x 4 + Terminal block x 1
	Long Backup Model	India socket x 2	India socket x 2 + Terminal block x 1	
Efficiency	Online Mode	88%	89%	90%
Battery Voltage	Standard Model	24 Vdc	48 Vdc	72 Vdc
	Long Backup Model	36 Vdc	72 Vdc	72 Vdc
Charger Current	Standard Model	1A		
	Long Backup Model	1/ 2/ 4/ 6A		
Audible Noise		< 50dBA @ 1 meter		
Display		LCD		
Communication Interfaces	Standard/ Long Backup	Mini Slot x 1, RS-232 Port x 1, USB Port x 1		
Dimensions (W x D x H)	Standard Model	282 x 145 x 220 mm	504 x 145 x 220 mm	421 x 190 x 318 mm
	Long Backup Model	282 x 145 x 220 mm	397 x 145 x 220 mm	
Weight	Standard Model	9 kg	16.5 kg	25 kg
	Long Backup Model	4.4 kg	7.3 kg	7.8 kg
Environment	Operating Temperature	0 ~ 40°C		
	Relative Humidity	20% ~ 90% (non-condensing)		

\* At 110 ~ 160 Vac, linear de-rating between 60 ~ 100% load is required.

\*\* De-rate capacity to 80% when the output voltage is adjusted to 200 Vac or 208 Vac.

Please refer to the rating label for the safety rating.

All specifications are subject to change without prior notice.



User-friendly LCD Panel



Standard models with in-built battery



Rear panel



Facility Monitoring Software - InfraSuite Device Master



Delta offers full range UPS solutions from 600 VA to 4000 kVA to fulfill your power security needs.



2007~ 2008 Forbes Asia's Fabulous 50



2009 Frost & Sullivan Green Excellence Award for Corporate Leadership



Delta's Manufacturing System Certified by ISO 9001 and ISO 14001 Standards



IECQ Certificate of Hazardous Substance Process Management

