

LINE INTERACTIVE UPS



LINE INTERACTIVE UPS **Legend** **1000**



COMPLETE PROTECTION
for
Computers and
Other IT Applications.

SALIENT FEATURES

- Top Grade Micro Processor based UPS - Optimum Reliability.
- Boost and Buck AVR - Ultimate Voltage Stabilization.
- In-Built 7AH x 2 Batteries.
- Protection against Overload, Discharge/ Overcharge.
- Wide INPUT Range 140V~300V AC.
- Auto Restart while AC is recovering.
- Generator Compatibility Option.
- Much Longer Battery Life.
- Easy Off-Mode Charging.
- Cold Start Function.

TECHNICAL SPECIFICATIONS

MODEL	UPS LEGEND 1000	
CAPACITY	1000VA / 600W	
INPUT	Voltage Range	140V~300V AC
	Frequency	50Hz ± 10%
OUTPUT	Voltage (Batt. Mode)	230V AC Nominal
	Frequency (Batt. Mode)	50Hz ± 1Hz
	Waveform (Batt. Mode)	Modified Sinewave
	Transfer Time	Typical 4~8ms
	Rating	1000VA (Max.)
BATTERY	Battery Type	SMF (Sealed Maintenance Free)
	DC V / AH / Nos.	12V / 7AH x 2 Batteries
	Recharge Time (Typ.)	6 Hrs to 90% after complete discharge
ENVIRONMENT: 0°~40°C, 0~90% RH Non-Condensing Noise Level <40dB		
PHYSICAL	Dimensions (mm)	315(L) x 130(W) x 183(H)
	Weight (Kgs.)	Net: 8.02Kgs. Gross: 8.60Kgs.
TECHNICAL FEATURES	Auto Switch Off in Battery Low is In-Built. Off Mode Charging & Overload Protection are In-Built.	

* Above specifications are measured under computer load.
* Specifications are subject to change without notice.