

www.exidereachout.com

EXIDEcare

1800 103 5454

INDIA'S NO.1 HEAVY VEHICLE BATTERY

**36-MONTH
WARRANTY***



INDIA MOVES ON **EXIDE**

*For conditions, visit exidereachout.com

EXIDE XPRESS



- **Withstands bumps and vibrations:** Special polypropylene container with strengthening ribs makes the battery strong enough to withstand severe operating conditions and arduous vibrations in service
- **Made for Indian environment:** Use of special Hybrid Alloy System ensures that the battery can withstand the Indian environment and high under-bonnet temperatures
- **Improved cycle life:** Double-clad separation in the form of a unique rib-free separator profile, reinforced with texturised glass mat, provides surface support to the active material, thereby improving cycle life and resistance to bumps and vibrations
- **Quick recharge:** Unique tree radial grid design, lower internal resistance and a special paste chemistry enhance recharging capability of the battery during use
- **Magic eye:** Easy to ascertain the state of the charge as well as electrolyte level of the battery
- **Enhanced safety:** Micro-porous filter disc in vent openings help arrest acid fumes and restrict spark propagation inside the battery
- **Leak-resistant design:** Side vented lid with electrolyte flow back system reduces chance of electrolyte leakage during handling
- **Maintenance-free:** Requires topping up only once in 6 months. Special alloy ensures low water loss during high temperature operations
- **Ready-to-use:** Batteries delivered factory-charged in ready-to-use condition

TECHNICAL SPECIFICATIONS OF EXIDE XPRESS RANGE OF BATTERIES

BATTERY TYPE	PART NUMBER	CAPACITY (AH) 20HR (REF)	MAXIMUM OVERALL DIMENSIONS			NOMINAL FILLED WEIGHT (KG)	ELECTROLYTE VOLUME (LITRE)	CHARGING CURRENT (A)	CCA AT -18°C AS PER		ACID LEVEL INDICATOR	BATTERY LAYOUT
			L (MM)	W (MM)	H (MM)				IEC	SAE		
XP800	FXP0-XP800	80	305	173	225	23.0	4.9	5.0	420	530	Present	
XP800L	FXP0-XP800L	80	305	173	225	23.0	4.9	5.0	420	530	Present	
XP880	FXP0-XP880	88	410	176	233	26.6	6.8	5.5	430	550	Present	
XP1000	FXP0-XP1000	100	410	176	233	28.1	6.3	6.5	475	580	Present	
XP1100	FXP0-XP1100	110	410	176	233	29.6	6.0	7.0	550	700	Present	
XP1300	FXP0-XP1300	130	505	182	257	35.1	8.3	9.0	560	720	Present	
XP1500	FXP0-XP1500	150	508	222	257	42.0	10.4	9.0	640	785	Present	
XP1800	FXP0-XP1800	180	521	278	270	55.1	15.9	13.0	830	1050	Present	
XP2000	FXP0-XP2000	200	521	278	270	56.8	15.5	14.0	910	1150	Present	

Authorised EXIDE Dealer

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continuous improvement and we reserve the right to change details without prior notice.